

Manufactured Since 1942 by: Apex Engineering Products Corporation

RYDLYME®

World's Leading Biodegradable Descaler

Pumping Systems

Circulate **RYDLYME** through your critical equipment to most effectively dissolve water scale deposits!



Apex Engineering Products Corporation proudly promotes Iwaki seal-less magnetic drive pumps and Iwaki Air high performance air-operated double diaphragm (AODD) pumps. These **RYDLYME** pumping systems are specifically designed to offer you the best chemical handling equipment available to help you maintain your facility in peak operating condition. For added convenience, high quality IPEX tru-union ball valves are equipped on all of our robust systems. The Iwaki magnetic drive pumps are powered by TEFC Weg motors that are CE approved and operate on single phase, 60 Hz, 115/230V and 3500 RPM. Select pump systems can be special ordered for 50 Hz power supplies.

The Iwaki Air AODD pump systems are ideally suited for high head **RYDLYME** cleaning applications, requiring air supply pressures from 20-100 PSI. These pumps are industry leaders and are known for durability and reliability. These seal-less and self-priming pumps are fitted with lubrication free air control valves, mufflers, filters, and regulators, for variable flow rates that even satisfy explosion proof requirements. For pricing and availability on our 2" and 3" sized pumps, please speak with one of our qualified technicians.



Model 10MDO & 15MDO

The 1" **Model 10MDO** Iwaki Magnetic Drive Pump Only is a seal-less ½ HP centrifugal type constructed with long lasting materials perfectly suited for **RYDLYME**. This unit weighs 46 pounds and comes with a 9' power supply cord and sturdy plastic base. It can operate up to 40 GPM or 51' head. The 1½" **Model 15MDO** unit is a ¾ HP pump that contains the same high quality attributes and expands capacity up to 75 GPM or 45' head.



Model 10MDC

The 1" Pump Complete model is utilized to easily clean your water fouled equipment. This system includes the **Model 10MDO** magnetic drive pump, three 1" diameter x 10' hoses, and bulkhead fittings all packaged in a 14-gallon recirculating bucket. The bucket comes predrilled for the bulkhead fittings and some minor assembly is required prior to use.



Model 15MDC

The 1½" Magnetic Drive Pump Cart system is our most versatile and convenient package. The **15MDO** is mounted on a 2' by 4' heavy-duty plastic cart with 8" swivel wheels. This high quality system includes a 30-gallon circulation bucket with a drain valve coupled via bulkhead fittings to multiple tru-union valves for simplistic operation. The pump is GFCI wired and operated by a switch in a mounted weatherproof electrical box complete with a 20' power cord. A by-pass system is hard piped into this unit to accommodate both small and large applications, as well as water flushing the unit upon job completion. This system is fully assembled, includes three 1½" diameter x 10' hoses and is ready for immediate use.



Model 10PPO & 15PPO

The Iwaki Air AODD pumps offer higher capacity and can easily handle lengthy discharge lines, high head pressures and large volumes. The 1" **Model 10PPO** Pneumatic Pump Only is extremely portable at 29 pounds. The 63 pound 1½" **Model 15PPO** Pneumatic Pump Only offers greater flow and head pressure. Also available are 2" and 3" pumps that can achieve even greater flow. **Model 10PPO** Max Flow Rate: 43 GPM Max Discharge Head: 230' **Model 15PPO** Max Flow Rate: 100 GPM Max Discharge Head: 230'



Model 10PPC

The 1" Pneumatic Pump Cart system is a versatile unit assembled on a 2' by 4' heavy-duty plastic cart with 8" swivel wheels. This high quality system contains a 30-gallon circulation bucket with a valved drain coupled via bulkhead fittings to multiple tru-union valves for simplistic operation. Also included are three 1" diameter x 10' hoses for quick setup and operation.



Model 10CIP

The "Clean-In-Place" (CIP) Compact Pumping System is designed for cleaning in confined or limited access areas. Features include a 15-gallon circulation bucket, three 1" diameter x 10' hoses, and a ½ HP 1" magnetic drive pump secured on a steel frame hand truck with 8" pneumatic wheels. The pump motor operates at 3500 RPM, 115/230V, 60 Hz and can achieve up to 40 GPM or 51' head.



Model 75LDP

The ¾" Liquid Drum Pump is offered as a fast and convenient tool, recommended for the ease of transferring **RYDLYME** from drums to your circulating system. This pump utilizes an 800-watt, 9000 RPM, 115V, 60 Hz motor fitted with a 39" polypropylene tube. This pump has flow rates up to 42 GPM making it an essential addition to your **RYDLYME** preventative maintenance programs.



Model RTK 350

The **RYDLYME** Tankless Kit is specifically designed for use on tankless water heaters. The **RTK** utilizes a submersible, ¾" magnetic drive pump capable of 5 GPM. The kit includes two 6' hoses, 5 gallon circulation bucket and retention clamp. One quart of **RYDLYME** Biodegradable Descaler is recommended per tankless water heater. The **RTK** includes two quarts to facilitate semi-annual cleanings.



1241 Shoreline Drive
Aurora, IL 60504
630-820-8888
630-820-8886 fax
www.ApexEngineeringProducts.com